

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION I: COMPANY IDENTIFICATION

DISTRIBUTOR'S NAME:	ECO-CORFLEX INDUSTRIAL POLYMERS		
ADDRESS:	4350 S. 38 TH ST., SUITE #110, PHOENIX, AZ 85040		
EMERGENCY PHONE #:	1-800-255-3924	DATE REVISED:	MAR 17, 2023
INFORMATION PHONE #:	1-866-406-2628	NAME OF PREPARER:	TECH. DEPT.

SECTION II: HAZARDS IDENTIFICATION

GLOBALY HARMONIZED SYSTEM (GHS)

CLASSIFICATION: HAZARDOUS

CARCINOGENICITY: CATEGORY 2

SKIN IRRITATION: CATEGORY 2

EYE IRRITATION: CATEGORY 2A

SKIN SENSITIZATION: SUB-CATEGORY 1B

ACUTE AQUATIC TOXICITY: CATEGORY 2

CHRONIC AQUATIC TOXICITY: CATEGORY 2

GHS LABEL ELEMENTS

HAZARD PICTOGRAMS



SIGNAL WORD: WARNING!

HAZARD STATEMENTS

H315+H320: CAN CAUSE EYE AND SKIN IRRITATION AND SENSITIZATION

H317: MAY CAUSE ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H351: SUSPECTED OF CAUSING CANCER

H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION II: HAZARDS IDENTIFICATION

PRECAUTIONARY STATEMENTS:

PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE

P273: AVOID RELEASE TO THE ENVIRONMENT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

RESPONSE

P302+P352: **IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P333+P313: IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

P391: COLLECT SPILLAGE

DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

OTHER HAZARDS

NO DATA AVAILABLE

SECTION III: COMPOSITION & INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

4,4'-ISOPROPYLDIPHENOL-EPOCHLOROXYDRIN COPOLYMER - WT: 60-100; CAS NUMBER: 025068-38-6

BENZYL ALCOHOL - WT: 5-10; CAS NUMBER: 000100-51-6

O-CRESYL GLYCIDYLETHER - WT: 1-5; CAS NUMBER: 002210-79-9

TITANIUM DIOXIDE - WT: 0-20; CAS NUMBER: 013463-67-7

IRON (III) OXIDE - WT: 0-10; CAS NUMBER: 001309-37-1

CARBON BLACK - WT: 0-10; CAS NUMBER: 001333-86-4

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION IV: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: 93°C (199°F) TCC

CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: LEL: ND UEL: ND

OSHA CLASS: NOT REGULATED

AUTO IGNITION TEMP: ND

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, ALDEHYDES, ACIDS

SENSITIVITY TO IMPACT: ND

SENSITIVITY TO STATIC DISCHARGE: ND

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. WATER SPRAY IS USEFUL IN COOLING FIRE-EXPOSED VESSELS AND IN DISPERSING VAPORS.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH OXIDIZING AGENT.

SECTION VI: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION VII: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT.

STORAGE: AVOID TEMPERATURE EXTREMES. STORE AWAY FROM EXCESSIVE HEAT, FROM SOURCES OF IGNITION AND FROM REACTIVE MATERIALS.

SECTION VII: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS (CAS)	EXPOSURE LIMITS (PPM)				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
025068-38-6	NE	NE	NE	NE	
000100-51-6	NE	NE	NE	NE	
002210-79-9	NE	NE	NE	NE	
013463-67-7	10MG/M3	ND	10MG/M3	ND	(SEE NOTE 1)
001309-37-1	5MG/M3	ND	5MG/M3	ND	(SEE NOTE 1)
001333-86-4 3.	5MG/M3	ND	3.5MG/M3	ND	(SEE NOTE 1)

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK. NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20PPM FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >120°C (199°F)

SPECIFIC GRAVITY: 1.1-1.2

VAPOR PRESSURE: < 0.13 kPa @ 20°C (68°F)

MELTING POINT: ND

VAPOR DENSITY (AIR = 1): ND

EVAPORATION RATE (BUTYL ACETATE = 1): <1

SOLUBILITY IN WATER: INSOLUBLE

pH: NA

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

ODOR THRESHOLD: ND

APPEARANCE AND ODOR: PIGMENTED LIQUID, MILD ODOR

% VOLATILES BY VOLUME: 0%

% SOLIDS BY WEIGHT: 100%

SECTION X: STABILITY & REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: NOT APPLICABLE (MATERIAL IS STABLE)

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PERCHLORATES, NITRATES), STRONG ACIDS, HYPOCHLORITES, PEROXIDES.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR.

SECTION XI: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

ACUTE ORAL TOXICITY

VERY LOW TOXICITY IF SWALLOWED. HARMFUL EFFECTS NOT ANTICIPATED FROM SWALLOWING SMALL AMOUNTS; LD₅₀, RAT >15,000 mg/kg

ACUTE DERMAL TOXICITY

PROLONGED SKIN CONTACT IS UNLIKELY TO RESULT IN ABSORPTION OF HARMFUL AMOUNTS; LD₅₀, RABBIT 23,000 mg/kg

ACUTE INHALATION TOXICITY

AT ROOM TEMPERATURE, EXPOSURE TO VAPOR IS MINIMAL DUE TO LOW VOLATILITY. VAPOR FROM HEATED MATERIAL, MIST OR AEROSOLS MAY CAUSE RESPIRATORY IRRITATION. LC₅₀ HAS NOT BEEN DETERMINED

SKIN CORROSION/IRRITATION

PROLONGED CONTACT MAY CAUSE SKIN IRRITATION WITH LOCAL REDNESS. REPEATED CONTACT MAY CAUSE SKIN IRRITATION WITH LOCAL REDNESS

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION XI: TOXICOLOGICAL INFORMATION (CONT'D)

SERIOUS EYE DAMAGE/EYE IRRITATION

MAY CAUSE EYE IRRITATION

CORNEAL INJURY IS UNLIKELY

SENSITIZATION

FOR SIMILAR MATERIAL(S):

HAS CAUSED ALLERGIC SKIN REACTIONS IN HUMANS

HAS DEMONSTRATED THE POTENTIAL FOR CONTACT ALLERGY IN MICE

FOR RESPIRATORY SENSITIZATION: NO RELEVANT DATA FOUND

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

EVALUATION OF AVAILABLE DATA SUGGESTS THIS MATERIAL IS NOT AN STOT-SE TOXICANT

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

EXCEPT FOR SKIN SENSITIZATION REPEATED EXPOSURES TO LOW MOLECULAR WEIGHT EPOXY RESINS OF THIS TYPE ARE NOT ANTICIPATED TO CAUSE ANY SIGNIFICANT ADVERSE EFFECTS.

CARCINOGENIC DATA: NTP: NONE OSHA: NONE IARC: 2B

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

SECTION XII: ECOLOGICAL INFORMATION

TOXICITY

ACUTE TOXICITY TO FISH

MATERIAL IS MODERATELY TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50 BETWEEN 1 AND 10 mg/l IN THE MOST SENSITIVE SPECIES TESTED)

LC50, ONCORHYNCHUS MYKISS (RAINBOW TROUT), SEMI-STATIC TEST. 96 HR, 2 mg/l

ACUTE TOXICITY TO AQUATIC INVERTEBRATES

EC50, DAPHNIA MAGNA (WATER FLEA), STATIC TEST, 48 HR, 1.8 mg/l

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS

ErC50, SCENEDESMUS CAPRICORNUTUM (FRESH WATER ALGAE), STATIC TEST, 72 HR, GROWTH RATE INHIBITION 11mg/L

TOXICITY TO BACTERIA

IC50, BACTERIA, 18 HR, RESPIRATION RATES > 42.6 mg/l

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION XII: ECOLOGICAL INFORMATION

CHRONIC AQUATIC TOXICITY

CHRONIC TOXICITY TO AQUATIC INVERTEBRATES

MATC (MAXIMUM ACCEPTABLE TOXICANT LEVEL), DAPHNIA MAGNA, SEMI STATIC TEST, 21 d,
NUMBER OF OFFSPRING, 0.55 mg/l

PERSISTANCE AND DEGRADABILITY

BIODEGRADABILITY: BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

10 DAY WINDOW: NA

BIODEGRADATION: 12%

EXPOSURE TIME: 28 DAYS

METHOD: OECD TEST GUIDELINE 302B OR EQUIVALENT

THEORETICAL OXYGEN DEMAND: 2.35 mg/mg ESTIMATED

PHOTODEGRADATION

TEST TYPE: HALF-LIFE (INDIRECT PHOTOLYSIS)

SENSITIZER: OH RADICALS

ATMOSPHERIC HALF-LIFE: 1.92 HR

METHOD: ESTIMATED

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: BIOCONCENTRATION POTENTIAL IS MODERATE (BCF BETWEEN 100 AND 3000 OR LOG POW BETWEEN 3 AND 5)

PARTITION COEFFICIENT: N-OCTANOL/WATER (LOG POW): 3.242 @25°C ESTIMATED

MOBILITY IN SOIL

POTENTIAL FOR MOBILITY IN SOIL IS LOW (K_{oc} BETWEEN 500 AND 2000)

GIVEN ITS VERY LOW HENRY'S CONSTANT, VOLATIZATION FROM NATURAL BODIES OF WATER OR MOIST SOIL IS NOT EXPECTED TO BE AN IMPORTANT FATE PROCESS

PARTITION COEFFICIENT (K_{oc}): 1800-4400 ESTIMATED

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION XIII: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: NOT A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV: TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: RESIN COMPOUND, NOT REGULATED

HAZARD CLASS: NA

UN NUMBER: NA PACKAGING

GROUP: NA

DOT PRODUCT RQ LBS (KGS): NA

HAZARD LABEL: NA

HAZARD PLACARD: NA

IMO SHIPPING DATA: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (EPOXY RESIN), 9, PGIII

ICAO/IATA SHIPPING DATA: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (EPOXY RESIN), 9, PGIII

ADDITIONAL INFORMATION: NONE

SECTION XV: REGULATORY INFORMATION

VOC: COMPONENT: 0 GRAMS/LITER

AS APPLIED: 0 GRAMS/LITER (PART OF MULTI-COMPONENT SYSTEM)

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION AND LIABILITY ACT): ND

SARA TITLE III

SECTION 312 HAZARD CLASS: IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

SECTION 313 LISTED INGREDIENTS: NONE ABOVE DE MINIMUS LEVELS

CALIFORNIA PROPOSITION 65: THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: CAS # 013463-67-7, CAS # 001333-86-4

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION XVI: OTHER INFORMATION

ABBREVIATIONS & ACRONYMS:

ACA - AMERICAN COATINGS ASSOCIATION

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

ATE - ACUTE TOXICITY ESTIMATE

BCF - BIOCONCENTRATION FACTOR

CAS - CHEMICAL ABSTRACTS SERVICE (DIVISION OF THE AMERICAN CHEMICAL SOCIETY)

CLP - REGULATION (EC) NO 1272/2008 ON CLASSIFICATION, LABELING AND PACKAGING OF SUBSTANCES AND MIXTURES

DOT - US DEPARTMENT OF TRANSPORTATION

EC - EUROPEAN COMMUNITY

EEC - EUROPEAN ECONOMIC COMMUNITY

EINECS- EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

EN - EUROPEAN STANDARD

EPA - ENVIRONMENTAL PROTECTION AGENCY (USA)

EU - EUROPEAN UNION

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS

HMIS - HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (USA)

HSDB - HAZARDOUS SUBSTANCES DATA BANK

IARC - INTERNATIONAL ASSOCIATION OF RADIO CARDIOLOGISTS

IATA - INTERNATIONAL AIR TRANSPORT ASSOCIATION

IBC - INTERMEDIATE BULK CONTAINER

ICAO - INTERNATIONAL CIVIL AVIATION ORGANIZATION

IMDG - INTERNATIONAL MARITIME CODE FOR DANGEROUS GOODS

LC - LETHAL CONCENTRATION

LD - LETHAL DOSE

LOLI - LIST OF LISTS

NA - NOT APPLICABLE

ND - NO DATA OR INFORMATION AVAILABLE

NE - NOT ESTABLISHED

NFPA - NATIONAL FIRE PROTECTION ASSOCIATION (USA)

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: 100% SOLIDS NON-MOISTURE - (PART A)

HMIS CODES: H F F

PRODUCT DESCRIPTION: NON-MOISTURE EPOXY (2A: 1B)

1 1 2

SECTION XVI: OTHER INFORMATION (CONT'D)

NTP - NATIONAL TOXICOLOGY PROGRAM (USA)

OECD - ORGANIZATION FOR ECONOMIC CO-OPERATION AND DEVELOPMENT

OEL - OCCUPATIONAL EXPOSURE LIMITS

OSHA - OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION (USA)

RID - REGULATIONS CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY RAIL

RTECS - REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES

RTK - RIGHT-TO-KNOW LAWS

SDS - SAFETY DATA SHEET

STEL - SHORT-TERM EXPOSURE LIMIT

TWA - TIME WEIGHTED AVERAGE

UN - UNITED NATIONS

WEL - WORKPLACE EXPOSURE LIMIT

DISCLAIMER

THE INFORMATION PROVIDED HEREIN WAS BELIEVED BY GFCFS TO BE ACCURATE AT THE TIME OF PREPARATION FROM SOURCES BELIEVED TO BE RELIABLE, BUT IT IS THE RESPONSIBILITY OF THE USER TO INVESTIGATE AND UNDERSTAND OTHER PERTINENT SOURCES OF INFORMATION, TO COMPLY WITH ALL LAWS AND PROCEDURES APPLICABLE TO THE SAFE HANDLING AND USE OF THE PRODUCT AND TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR IT'S INTENDED USE. ALL PRODUCTS DISTRIBUTED BY GFCFS ARE SUBJECT TO GFCFS'S TERMS AND CONDITIONS OF SALE. GFCFS MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY GFCFS, EXCEPT THAT THE PRODUCT SHALL CONFORM TO SPECIFICATIONS. NOTHING CONTAINED HEREIN CONSTITUTES AN OFFER FOR THE SALE OF ANY PRODUCT.