

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION I: COMPANY IDENTIFICATION

DISTRIBUTOR'S NAME:	ECO-CORFLEX INDUSTRIAL POLYMERS		
ADDRESS:	3801 E. ROESER ROAD, SUITE #1, PHOENIX, AZ 85040		
EMERGENCY PHONE #:	1-800-255-3924	DATE REVISED:	MAR 07, 2016
INFORMATION PHONE #:	1-866-406-2628	NAME OF PREPARER:	TECH. DEPT.

SECTION II: HAZARDS IDENTIFICATION

OSHA / HCS STATUS: THIS MATERIAL IS CONSIDERED HAZARDOUS BY THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE: RESPIRATORY TRACT IRRITATION (CATEGORY 3).

ACUTE INHALATION (VAPOR AND MIST) TOXICITY (CATEGORY 4).

RESPIRATORY SENSITIZATION (CATEGORY 1).

SPECIFIC TARGET ORGAN TOXICITY, REPEATED EXPOSURE (INHALATION): LUNGS (CATEGORY 2).

SKIN SENSITIZATION (CATEGORY 1).

PERCENTAGE OF MIXTURE CONSISTING OF INGREDIENTS OF UNKNOWN TOXICITY: 100%.

HAZARD PICTOGRAMS:

EXCLAMATION MARK (IRRITANT).

HEALTH HAZARD (HEALTH HAZARD).

SIGNAL WORD.....: DANGER!

HAZARDOUS STATEMENTS:

H317: MAY CAUSE AN ALLERGIC SKIN REACTION.

H332: HARMFUL IF INHALED.

H334: MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.

H335: MAY CAUSE RESPIRATORY IRRITATION.

H373: MAY CAUSE DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED EXPOSURE.

GENERAL PRECAUTIONARY STATEMENTS:

PREVENTION:

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P280: WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION. P284: [IN CASE OF INADEQUATE VENTILATION] WEAR RESPIRATORY PROTECTION.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION II: HAZARDS IDENTIFICATION (CONT'D)

RESPONSE:

P301 + P310 + 331: IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER/DOCTOR. DO NOT INDUCE VOMITING.

P303 + P361 + P353: IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER [OR SHOWER].

P304 + P340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

P305 + P351 + P338: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

P332 + P313: IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION.

P337 + P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

P362 + P364: TAKE OFF CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE.

P370 + P378: IN CASE OF FIRE: USE DRY CHEMICAL, CO₂, WATER FOG/MIST, OR FOAM TO EXTINGUISH.

STORAGE:

P233: KEEP CONTAINER TIGHTLY CLOSED.

P403 + P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P405: STORE LOCKED UP.

DISPOSAL:

P501: DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

SUPPLEMENTAL LABEL ELEMENTS:

WARNING! INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST.

HAZARDS NOT OTHERWISE CLASSIFIED:

A HISTORY OF ECZEMA OR RESPIRATORY ALLERGIES SUCH AS HAY FEVER, ARE POSSIBLE REASONS FOR EXCLUSION FROM ISOCYANATE WORK AREAS. APPLICANTS WITH A HISTORY OF PRIOR ISOCYANATE SENSITIZATION SHOULD BE EXCLUDED FROM FURTHER WORK WITH ISOCYANATES. A COMPREHENSIVE ANNUAL MEDICAL SURVEILLANCE PROGRAM SHOULD BE INSTITUTED FOR ALL EMPLOYEES WHO ARE POTENTIALLY EXPOSED TO DIISOCYANATES. ONCE A WORKER HAS BEEN DIAGNOSED AS SENSITIZED TO ANY ISOCYANATE, NO FURTHER EXPOSURE SHOULD BE PERMITTED.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION III: COMPOSITION & INFORMATION ON INGREDIENTS

SUBSTANCE / MIXTURE: MIXTURE

OTHER MEANS OF IDENTIFICATION (COMPOSITION): NOT AVAILABLE

COMPONENT	CAS #	% BY WEIGHT
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	100.0

THERE ARE NO ADDITIONAL INGREDIENTS PRESENT WHICH, WITHIN THE CURRENT KNOWLEDGE OF THE SUPPLIER AND IN THE CONCENTRATIONS APPLICABLE, ARE CLASSIFIED AS HAZARDOUS TO HEALTH OR THE ENVIRONMENT AND HENCE REQUIRE REPORTING IN THIS SECTION.

SECTION IV: FIRST AID MEASURES

EYE CONTACT: IN CASE OF CONTACT, FLUSH EYES WITH PLENTY OF LUKEWARM WATER. USE FINGERS TO ENSURE THAT EYELIDS ARE SEPARATED AND THE EYE IS BEING IRRIGATED. REMOVE CONTACTS IF POSSIBLE. GET MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, ADMINISTER CPR UNTIL HELP ARRIVES OR THE VICTIM STARTS TO BREATHE ON HIS OWN. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SEEK MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT: IMMEDIATELY WASH WITH SOAP AND WATER AND RINSE THOROUGHLY. REMOVE CONTAMINATED CLOTHING. IF SKIN IRRITATION CONTINUES, CONSULT A DOCTOR.

INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING UNLESS DIRECTED TO BY MEDICAL PERSONNEL. GET MEDICAL ATTENTION.

POTENTIAL HEALTH EFFECTS: ISOCYANATE VAPORS OR MIST AT CONCENTRATIONS ABOVE THE EXPOSURE LIMITS OR GUIDELINES CAN IRRITATE (BURNING SENSATION) THE MUCOUS MEMBRANES IN THE RESPIRATORY TRACT (NOSE, THROAT, LUNGS) WITH SYMPTOMS OF RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION (BREATHING DIFFICULTY). PERSONS WITH A PREEXISTING, NONSPECIFIC BRONCHIAL HYPERACTIVITY CAN RESPOND TO CONCENTRATIONS BELOW THE EXPOSURE LIMITS OR GUIDELINES WITH SIMILAR SYMPTOMS AS WELL AS ASTHMA ATTACK OR ASTHMA-LIKE SYMPTOMS. EXPOSURE ABOVE THE EXPOSURE LIMITS OR GUIDELINES MAY LEAD TO BRONCHITIS, BRONCHIAL SPASM AND PULMONARY EDEMA (FLUID IN LUNGS). CHEMICAL OR HYPERSENSITIVITY PNEUMONITIS, WITH FLU-LIKE SYMPTOMS (E.G. FEVER, CHILLS), HAS ALSO BEEN REPORTED. THESE SYMPTOMS CAN BE DELAYED UP TO SEVERAL HOURS AFTER EXPOSURE. THESE EFFECTS ARE USUALLY REVERSIBLE. MAY CAUSE SKIN IRRITATION WITH SYMPTOMS OF REDDENING, ITCHING AND SWELLING. CAN CAUSE SENSITIZATION. PERSONS PREVIOUSLY SENSITIZED CAN EXPERIENCE ALLERGIC SKIN REACTION WITH SYMPTOMS OF REDDENING, ITCHING, SWELLING AND RASH. CURED MATERIAL IS DIFFICULT TO REMOVE. MAY CAUSE EYE IRRITATION WITH SYMPTOMS OF REDDENING, TEARING, STINGING, AND SWELLING.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**

PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B)

2 1 1

SECTION IV: FIRST AID MEASURES (CONT'D)

MAY CAUSE TEMPORARY CORNEAL INJURY. VAPOR OR AEROSOL MAY CAUSE IRRITATION WITH SYMPTOMS OF BURNING AND TEARING. MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT; SYMPTOMS MAY INCLUDE ABDOMINAL PAIN NAUSEA, VOMITING, AND DIARRHEA.

OVER-EXPOSURE SIGNS / SYMPTOMS: SYMPTOMS OF OVER EXPOSURE CONSIST OF RUNNING NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. REDDENING, ITCHING, SWELLING, AND RASH ON SKIN. EYES MAY SHOW SYMPTOMS OF REDDENING, TEARING, STINGING, AND SWELLING. SYMPTOMS OF DIGESTIVE IRRITATION INCLUDE ABDOMINAL PAIN, NAUSEA, VOMITING, AND DIARRHEA.

NOTE TO PHYSICIAN: TREAT SYMPTOMATICALLY.

SECTION V: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: DRY CHEMICAL, CO₂, OR FOAM USE WATER SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL.

UNSUITABLE EXTINGUISHING MEDIA: WATER FULL JET.

HAZARDOUS COMBUSTION PRODUCTS: CARBON OXIDES, DENSE BLACK SMOKE, HYDROGEN CYANIDE, ISOCYANATE, ISOCYANIC ACID, OTHER UNDETERMINED COMPOUNDS.

OTHER CONSIDERATIONS: CLOSED CONTAINER MAY FORCIBLY RUPTURE UNDER EXTREME HEAT OR WHEN CONTENTS ARE CONTAMINATED WITH WATER. USE COLD-WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS TO MINIMIZE THE RISK OF RUPTURE. LARGE FIRES CAN BE EXTINGUISHED WITH LARGE VOLUMES OF WATER APPLIED FROM A SAFE DISTANCE, SINCE REACTION BETWEEN WATER AND HOT DIISOCYANATE CAN BE VIGOROUS.

FIRE FIGHTING PROCEDURES: AVOID CONTACT WITH PRODUCT. DURING A FIRE, ISOCYANATE VAPORS AND OTHER IRRITATING, HIGHLY TOXIC GASES MAY BE GENERATED BY THERMAL DECOMPOSITION OR COMBUSTION. EXPOSURE TO HEATED DIISOCYANATE CAN BE EXTREMELY DANGEROUS.

FIRE FIGHTING EQUIPMENT: FIREFIGHTERS SHOULD WEAR NFPA COMPLIANT STRUCTURAL FIREFIGHTING PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS AND NFPA COMPLIANT HELMET, HOOD, BOOTS, AND GLOVES. DECONTAMINATE EQUIPMENT AND PROTECTIVE CLOTHING PRIOR TO REUSE.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**

PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION VI: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION: WEAR APPROPRIATE PPE. EVACUATE SURROUNDING AREAS AND ISOLATE THE AREA. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. PROVIDE ADEQUATE VENTILATION. WEAR APPROPRIATE RESPIRATOR WHEN VENTILATION IS INADEQUATE.

ENVIRONMENTAL PRECAUTIONS: AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF AND CONTACT WITH SOIL, WATERWAYS, DRAINS AND SEWERS. INFORM THE RELEVANT AUTHORITIES IF THE PRODUCT HAS CAUSED ENVIRONMENTAL POLLUTION (SEWERS, WATERWAYS, SOIL OR AIR).

METHODS FOR CONTAINMENT & CLEAN-UP: ABSORB WITH LIQUID-BINDING MATERIAL (SAND, DIATOMITE, ACID BINDERS, UNIVERSAL BINDERS, SAWDUST). SHOVEL INTO SUITABLE RECEPTACLES. DECONTAMINATE THE SPILL SURFACE USING A NEUTRALIZATION SOLUTION (90% FANTASTIC HEAVY DUTY ALL PURPOSE CLEANER AND 10% HOUSEHOLD AMMONIA) SCRUB THE SURFACE WITH BROOM OR BRUSH. WAIT AT LEAST 15 MINUTES AFTER APPLYING THE DECONTAMINATE SOLUTION AND COVER THE AREA WITH ABSORBENT AND SHOVEL INTO RECEPTACLE. KEEP THE LID OF RECEPTACLE LOOSE TO ALLOW CARBON DIOXIDE AND HEAT TO ESCAPE. DISPOSE OF CONTAINER AFTER 72 HOURS IN ACCORDANCE WITH EXISTING FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION VII: HANDLING AND STORAGE

PROTECTIVE MEASURES FOR HANDLING: INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR ALLERGIC REACTIONS TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. DO NOT BREATHE VAPORS, MIST, OR DUST. USE ADEQUATE VENTILATION. FLAMMABLE LIQUID. AVOID HEAT, SPARKS AND OPEN FLAMES. PUT ON APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOR AND CONTACT WITH EYES, SKIN AND CLOTHING. DO NOT LEAVE CONTAINERS OPEN. AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. EMPTY CONTAINERS RETAIN RESIDUE. OBSERVE ALL SAFETY PRECAUTIONS. DO NOT REUSE CONTAINER.

ADVICE ON GENERAL OCCUPATIONAL HYGIENE: WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. USE GENERAL INDUSTRIAL HYGIENE PRACTICE. WASH HANDS AFTER HANDLING PAINT/COATING AND BEFORE EATING, DRINKING OR SMOKING. READ AND UNDERSTAND ENTIRE SDS BEFORE HANDLING PRODUCT.

CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES): STORE IN AREA DESIGNATED FOR STORAGE OF FLAMMABLE LIQUID (SEE NFPA 30 AND OSHA 29 CFR 1910.106) IN ACCORDANCE WITH LOCAL REGULATIONS AWAY FROM SOURCES OF HEAT, IGNITION, AND DIRECT SUNLIGHT. STORE IN THE ORIGINAL CONTAINER. KEEP IN A DRY, WELL-VENTILATED AREA, AND AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10). KEEP CONTAINER TIGHTLY CLOSED AND SEALED UNTIL READY FOR USE. CONTAINERS THAT HAVE BEEN OPENED MUST HAVE A DRY NITROGEN BLANKET APPLIED BEFORE RESEALING. DO NOT STORE IN UNLABELED, UNAPPROVED OR REACTIVE CONTAINERS. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION VIII: EXPOSURE CONTROLS / PERSONAL PROTECTION

COMPONENT	CAS #	% BY WEIGHT
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	100.0
ACGIH/TLV : 0.005 pm TWA		
OSHA/PEL : 0.005 pm TWA		

ENGINEERING CONTROLS: USE ONLY WITH ADEQUATE VENTILATION. DO NOT BREATHE VAPORS. GENERAL DILUTION AND LOCAL EXHAUST AS NECESSARY TO CONTROL AIRBORNE VAPORS, MISTS, DUSTS, AND THERMAL DECOMPOSITION PRODUCTS BELOW APPROPRIATE AIRBORNE CONCENTRATION STANDARDS AND GUIDELINES. ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. USE AN EXPLOSION PROOF FAN TO ENSURE ADEQUATE VENTILATION ESPECIALLY IN CONFINED WORK AREA. CURING OVENS MUST BE VENTILATED TO PREVENT THE BUILD-UP OF EXPLOSIVE ATMOSPHERES AND TO PREVENT OFF GASES FROM ENTERING THE WORK PLACE.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: IF YOU EXPERIENCE EYE WATERING, HEADACHE OR DIZZINESS OR IF AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE ABOVE APPLICABLE LIMITS, WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH APPROVED) DURING AND AFTER APPLICATION. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE.

SKIN & BODY PROTECTION: IMPERVIOUS CHEMICAL RESISTANT GLOVES. LONG SLEEVED CLOTHING OR PROTECTIVE SLEEVES. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE & FACE PROTECTION: SPLASH PROOF CHEMICAL RESISTANT SAFETY GLASSES. WEAR IN COMBINATION WITH A FULL FACE SHIELD IF A SPLASH HAZARD EXISTS.

WORK HYGIENIC PRACTICES: WASH HANDS, FOREARMS AND FACE THOROUGHLY AFTER HANDLING CHEMICAL PRODUCTS, BEFORE EATING AND DRINKING, SMOKING OR USING THE LAVATORY AND AT THE END OF THE WORKING PERIOD. CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED WORN OUT OF THE WORKPLACE. WASH CONTAMINATED CLOTHING BEFORE REUSING. ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE CLOSE TO THE WORKSTATION LOCATION.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: LIQUID

COLOR: CLEAR TO SLIGHTLY YELLOW

ODOR: SLIGHT

ODOR THRESHOLD: NOT AVAILABLE

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES (CONT'D)

pH: NOT APPLICABLE
MELTING POINT: NOT AVAILABLE
FREEZING POINT: NOT AVAILABLE
INITIAL BOILING POINT: DECOMPOSES
FLASH POINT: 338° F
EVAPORATION RATE: NOT AVAILABLE
EXPLOSION LIMITS: LOWER & UPPER EXPLOSIVE LIMIT: NOT AVAILABLE
VAPOR PRESSURE: NOT AVAILABLE
VAPOR DENSITY (AIR = 1): NOT AVAILABLE
SPECIFIC GRAVITY (g/cc): 1.16
DENSITY (lb/gal): 9.68 lb/gl
SOLUBILITY IN WATER: REACTS
PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE
VISCOSITY: 63 – 65 SEC ZAHN 2
AUTO-IGNITION TEMPERATURE: NOT AVAILABLE
DECOMPOSITION TEMPERATURE: NOT AVAILABLE
ACTUAL V.O.C.: 0.0 lb/gl; (METRIC): 0 g/l
REGULATORY V.O.C.: 0.0 lb/gl; (METRIC): 0 g/l
OTHER PHYSICAL PROPERTIES: NOT AVAILABLE

SECTION X: STABILITY & REACTIVITY DATA

CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS.
POSSIBLE HAZARDOUS REACTIONS: CONTACT WITH MOISTURE, OTHER MATERIALS THAT REACT WITH ISOCYANATES, OR TEMPERATURES ABOVE 350°F MAY CAUSE POLYMERIZATION.
CONDITIONS TO AVOID: HEAT, FLAMES, AND SPARKS. PROTECT FROM FREEZING.
INCOMPATIBLE MATERIALS: WATER, AMINES, STRONG BASES, ALCOHOLS, COPPER ALLOYS.
HAZARDOUS DECOMPOSITION: CARBON OXIDES, DENSE BLACK SMOKE, HYDROGEN CYANIDE, ISOCYANATE, ISOCYANIC ACID, OTHER UNDETERMINED COMPOUNDS.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION XI: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

THE ACUTE EFFECTS OF THIS PRODUCT AS A WHOLE HAVE NOT BEEN TESTED.

DATA ON INDIVIDUAL COMPONENTS ARE BELOW:

ACUTE TOXICITY:

HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE (28182-81-2)

LD50 ORAL RAT, FEMALE > 2,500 mg/kg

LC50 INHALATION RAT, FEMALE 0.390 - 0.543 mg/l (4 HR.)

LD50 DERMAL RABBIT >2,000 mg/kg

CARCINOGENICITY: NO SUSPECTED CARCINOGENS PRESENT AT >0.1%

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVEL GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY OSHA.

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVEL GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT LEVEL GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY NTP.

EFFECTS OF ACUTE EXPOSURE FROM EYE CONTACT: MAY CAUSE SLIGHT SKIN AND EYE IRRITATION. SKIN SENSITIZER.

EFFECTS OF ACUTE EXPOSURE FROM SKIN CONTACT: NO DATA AVAILABLE.

EFFECTS OF ACUTE EXPOSURE FROM INGESTION: NO DATA AVAILABLE

EFFECTS OF ACUTE EXPOSURE FROM INHALATION: RESPIRATORY SENSITIZER. MAY CAUSE RESPIRATORY IRRITATION.

EFFECTS OF CHRONIC EXPOSURE: THERE IS NO INFORMATION ON THE CHRONIC EFFECTS OF REPEATED OR PROLONGED EXPOSURE.

PRIMARY ROUTE(S) OF ENTRY: EYE CONTACT, SKIN CONTACT, INGESTION, INHALATION

SECTION XII: ECOLOGICAL INFORMATION

ENVIRONMENTAL TOXICITY: ECOLOGICAL EVALUATION OF THIS MATERIAL HAS NOT BEEN PERFORMED; HOWEVER, DO NOT ALLOW THE PRODUCT TO BE RELEASED TO THE ENVIRONMENT WITHOUT GOVERNMENTAL APPROVAL/PERMITS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**

PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION XIII: DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: GENERATION OF WASTE SHOULD BE AVOIDED OR MINIMIZED WHENEVER POSSIBLE. DISPOSAL OF THIS PRODUCT SHOULD ALWAYS COMPLY WITH THE REQUIREMENTS OF ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL LEGISLATION AND ANY REGIONAL LOCAL AUTHORITY REQUIREMENTS. DISPOSE OF SURPLUS AND NON-RECYCLABLE PRODUCTS VIA A LICENSED WASTE DISPOSAL CONTRACTOR. THE MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY. CARE SHOULD BE TAKEN WHEN HANDLING EMPTIED CONTAINERS THAT HAVE NOT BEEN CLEANED OR RINSED OUT. EMPTY CONTAINERS MAY RETAIN SOME PRODUCT RESIDUES. AVOID DISPERSAL OF SPILLED MATERIAL AND RUNOFF/CONTACT WITH SOIL, WATERWAYS, DRAINS, & SEWERS.

SECTION XIV: TRANSPORTATION INFORMATION

TRANSPORTATION INFORMATION DISCLAIMER: DETERMINATION OF PROPER SHIPPING IDENTIFICATION IS DEPENDENT UPON THE FORM, QUANTITY AND PACKAGING. THE PERSON OFFERING A HAZARDOUS MATERIAL FOR TRANSPORT HAS THE SOLE RESPONSIBILITY TO PROPERLY PREPARE THE SHIPPING PAPER AND PACKAGING FOR TRANSPORT. PEOPLE LOADING AND UNLOADING MUST BE TRAINED ON ALL OF THE RISKS DERIVING FROM HANDLING THIS PRODUCT.

SECTION XV: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CLEAN AIR ACT SECTION 112(B) HAZARDOUS AIR POLLUTANTS (HAP'S): NO COMPONENTS PRESENT AT LEVELS HIGHER THEN 1% LISTED ON HAPS LIST OF CHEMICALS.

CERCLA: SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTION 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES: ACUTE HEALTH HAZARD. CHRONIC HEALTH HAZARD.

EPA SECTION 313: THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENT WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DE MIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

US STATE REGULATIONS:

CALIFORNIA PROPOSITION 65: THIS PRODUCT DOES NOT CONTAIN A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**
PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION XVI: OTHER INFORMATION

ABBREVIATIONS & ACRONYMS:

ACA - AMERICAN COATINGS ASSOCIATION
ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
ATE - ACUTE TOXICITY ESTIMATE
BCF - BIOCONCENTRATION FACTOR
CAS - CHEMICAL ABSTRACTS SERVICE (DIVISION OF THE AMERICAN CHEMICAL SOCIETY)
CLP - REGULATION (EC) NO 1272/2008 ON CLASSIFICATION, LABELING AND PACKAGING OF SUBSTANCES AND MIXTURES
DOT - US DEPARTMENT OF TRANSPORTATION EC - EUROPEAN COMMUNITY
EEC - EUROPEAN ECONOMIC COMMUNITY
EINECS- EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES
EN - EUROPEAN STANDARD
EPA - ENVIRONMENTAL PROTECTION AGENCY (USA)
EU - EUROPEAN UNION
GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS
HMIS - HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (USA)
HSDB - HAZARDOUS SUBSTANCES DATA BANK
IARC - INTERNATIONAL ASSOCIATION OF RADIO CARDIOLOGISTS
IATA - INTERNATIONAL AIR TRANSPORT ASSOCIATION
IBC - INTERMEDIATE BULK CONTAINER
ICAO - INTERNATIONAL CIVIL AVIATION ORGANIZATION
IMDG - INTERNATIONAL MARITIME CODE FOR DANGEROUS GOODS
LC - LETHAL CONCENTRATION
LD - LETHAL DOSE
LOLI - LIST OF LISTS
NA - NOT APPLICABLE
ND - NO DATA OR INFORMATION AVAILABLE
NE - NOT ESTABLISHED
NFPA - NATIONAL FIRE PROTECTION ASSOCIATION (USA)
NTP - NATIONAL TOXICOLOGY PROGRAM (USA)
OECD - ORGANIZATION FOR ECONOMIC CO-OPERATION AND DEVELOPMENT

ECO CorFlex

Molecular Industrial Polymers

SAFETY DATA SHEET

PRODUCT NAME: POLY – POLY HYBRID – CLEAR (PART B) **HMIS RATINGS: H F PH**

PRODUCT DESCRIPTION: SLOW & FAST CURE (3A: 2B) 2 1 1

SECTION XVI: OTHER INFORMATION (CONT'D)

OEL - OCCUPATIONAL EXPOSURE LIMITS

OSHA - OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION (USA)

RID - REGULATIONS CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY RAIL

RTECS - REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES

RTK - RIGHT-TO-KNOW LAWS

SDS - SAFETY DATA SHEET

STEL - SHORT-TERM EXPOSURE LIMIT

TWA - TIME WEIGHTED AVERAGE

WEL - WORKPLACE EXPOSURE LIMIT

DISCLAIMER

THE INFORMATION PROVIDED HEREIN WAS BELIEVED BY GFCFS TO BE ACCURATE AT THE TIME OF PREPARATION FROM SOURCES BELIEVED TO BE RELIABLE, BUT IT IS THE RESPONSIBILITY OF THE USER TO INVESTIGATE AND UNDERSTAND OTHER PERTINENT SOURCES OF INFORMATION, TO COMPLY WITH ALL LAWS AND PROCEDURES APPLICABLE TO THE SAFE HANDLING AND USE OF THE PRODUCT AND TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR IT'S INTENDED USE. ALL PRODUCTS DISTRIBUTED BY GFCFS ARE SUBJECT TO GFCFS'S TERMS AND CONDITIONS OF SALE. GFCFS MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY GFCFS, EXCEPT THAT THE PRODUCT SHALL CONFORM TO SPECIFICATIONS. NOTHING CONTAINED HEREIN CONSTITUTES AN OFFER FOR THE SALE OF ANY PRODUCT.